



NACHI BEARING INDIA PRIVATE LTD.

SR35SB1UU(GK) THK Radial Linear Guide (Block Only) Interchangeable SR Series

Bearing No. SR35SB1UU(GK)

| | |
|---|--------------------------------|
| Days to Ship | 4 Days |
| RoHS | 10 |
| Block Type | [Wide Short] SB: Short Compact |
| Nominal Part Number | 35 |
| Rail Type | Standard |
| Mounting Height M | 48 mm |
| Material | Carbon Steel |
| Radial Clearance | Normal |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 40900 |
| Basic Load Rating Static Rating Co(N) | 46700 |
| Allowable Static Moment MA(N m) | 275 |
| Allowable Static Moment MB(N m) | 171 |
| Allowable Static Moment MC(N m) | 615 |
| Block Mounting Hole Pitch (Width Direction) | 82 mm |
| Block Mounting Hole Diameter | 9 |
| Rail Mounting Hole Pitch | 80 mm |
| Rail Mounting Hole Diameter | 9 |
| Symbols for Dust Resistance | UU: End seals |
| | |

SR35SB1UU(GK) Bearing 2D drawings and 3D CAD models



NACHI BEARING INDIA PRIVATE LTD.

| | |
|--|------------|
| Block external dimension W | 100 mm |
| Block external dimension L | 77.6 mm |
| Mounting hole for blocks | Thru Holes |
| Number of Block Mounting Holes(holes) | 2 |
| Mounting Hole Dimension H(\varnothing) | 9 |
| Mounting Hole Screw Depth | Through mm |
| Block dimension L1 | 45.7 mm |